

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **2003307496 A**

(43) Date of publication of application: **31.10.2003**

(51) Int. Cl. **G01N 21/85**

(21) Application number: **2002113743**

(22) Date of filing: **16.04.2002**

(71) Applicant: **ISHIKAWAJIMA CONSTR MACH
CO**

(72) Inventor: **KOBAYASHI SAKAE**

(54) AGGREGATE DISCRIMINATING APPARATUS FOR CONCRETE

COPYRIGHT: (C)2004,JPO

(57) Abstract:

PROBLEM TO BE SOLVED: To accurately discriminate the grain size of aggregate for concrete without being affected by external factors.

SOLUTION: An acceptance hopper 4 is installed at the upper section of a transport surface 2a at the upstream side of a transport belt conveyor 2. A flow rate adjustment plate 8a is provided at the section of an exhausting port 4a of the acceptance hopper 4, and the height of the aggregate 1 for concrete that is exhausted from the acceptance hopper 4 is made uniform for feeding downstream. The transparent surface 2a at the downstream side of the acceptance hopper 4 of the transport belt conveyor is set to be a measurement region A. The measurement region A is covered with a shielding hood 7. A luminaire 13 and a CCD camera 18 are installed at the shielding hood 7. The aggregate 1 for concrete that is carried to the measurement region A is imaged by the CCD camera 17, and the data are processed by an image-processing unit.

